Dr. Bilger Umweltconsulting GmbH

Supersedes edition of: 15.01.2009

version: 1.0 /ENG

date of print: 22.11.2023 page 1 of 9

MATERIAL SAFETY DATA SHEET

compliant with regulations Version (EC) No 1907/2006 (REACH)

1. Identification of the substance/preparation and of the company

1.1 Identification of the substance/preparation

Trade name:

Sodium on inorganic carrier REACH registration No.

(Sodium): 01-2119484805-27-0002 (Aluminiumoxid): 01-2119529248-35

1.2 Use of the substance/preparation

Identified use:

Drying reagent for organic solvents

This number is only active during normal opening hours.

1.3 Identification of the company

supplier /producer/ importer/user/ trader e-Mail	Dr. Bilger Umweltconsulting GmbH Gewerbepark Birkenhain 7a D-63579 Freigericht Telefon: +49-(0)6051-9166951 info@bilgergmbh.de
Emergency telephone:	Tel.: +49-(0)6051-91669-51

1.4

Note:

Information Munich: +49/ (0)89 19240 **Emergency support**

2. **Hazards identification**

2.1 **Classification:**

Regulation (EG) No. 1272/2008,	
Hazard class/- category	Hazard notes
in contact with water releases	H260
flammable gases which may	
ignite spontaneously	
Causes severe skin burns and eye	H314
damage.	

2.2 Additional hazard notes concerning humans and environment:



e Dr. Bilger Umweltconsulting GmbH

Supersedes edition of: 15.01.2009

version: 1.0 /ENG

date of print: 22.11.2023 page 2 of 9

Hazard statements

H260 H314	in contact with water releases flammable gases which may ignite spontaneously Causes severe skin burns and eye damage.		
EUH014	reacts violently with water		
Precautionary statements:	Precautionary statements:		
Precaution			
P280	Wear protective gloves/ protective clothing/ eye protection/ face		
	protection.		
Response			
P301+P330+P331 P305+P351+P338	IF SWALLOWED: Rinse mouth. DO NOT induce vomiting IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continuous rinsing.		
P370+P378 P308+P311	In case of fire: Use metal fire powder for extinction. NO WATER. IF exposed or concerned: immediately call a POISON CENTER or		
F 300+F 311	doctor/physician.		
Storage			

P402+P404 S	Store in a dry place.	Store in a closed container
-------------	-----------------------	-----------------------------

3. <u>Compostion / Information on ingredients</u>

3.1 Information on substance: inorganic pellets with approx. 20% sodium

	Sodium (approx. 20%)	Aluminium oxide /approx. 80%)
Formel: CAS-Nr.: EG-Nr.: EINECS: Index-Nr.: REACH-Nummer:	Na 7440-23-5 213-132-9 231-132-9 011-001-00-0 01-2119484805-27-0002	Al₂O₃ 1344-28-1 215-691-6 01-2119529248-35

4. First aid measures



4.1 Description of First aid measures

General information:	Remove contaminated clothing immediately. In case of health Consult a doctor if health problems occur.
After inhalation:	Move immediately to fresh air after inhalation of smoke produced by the reactions. If unconscious, keep on the side and seek medical advice. Remove to fresh air. Oxygen or artificial respiration if necessary. Call a doctor immediately.

Supersedes edition of: 15.01.2009

version: 1.0 /ENG

date of print: 22.11.2023 page 3 of 9

After skin contact:	Remove metal with spatula and then rinse with plenty of water. In case of contact with liquid sodium, remove clothing immediately, Remove sodium with dry cloth, wash with plenty of water, consult a doctor.
After eye contact:	Immediately remove metal carefully. Remove contact lenses. Then rinse thoroughly with Rinse thoroughly with plenty of water until a doctor arrives.
After ingestion:	Do NOT induce vomiting. Rinse out mouth. Give plenty of water to drink; Consult a doctor immediately.
Notes for physician:	Medical treatment according to alkali burn. Show this safety data sheet to the doctor in attendance.

4.2 Most important symptoms and effects, both acute and delayed.

Symptoms: Ingestion may cause the following symptoms: Burning, Pain, Diarrhoea, Vomiting, Decreased blood pressure, Respiratory problems, Symptoms may be delayed.

Inhalation may cause the following symptoms: Irritating to respiratory system, altered lung function or difficulty breathing.

Skin contact may cause the following symptoms: Burn

Eye contact may cause the following symptoms: Burn

Health effects from repeated exposure may include: Irritation of the respiratory system.

4.3 Indication of any immediate medical attention and special treatment needed.

Treatment: Delayed rupture or constriction of the gastrointestinal tract may occur after ingestion. Close monitoring is recommended.

5. <u>Fire fighting measures</u>

5.1 Extinguishing Media

Suitable: Dry soda ash, Extinguishing powder class D, dry salt, dry concrete

Unsuitable: Water, CO₂, extinguishing agents class A, B, C, E and foam

5.2 Special hazards arising from substance or mixture

Emits toxic fumes under fire conditions. Material readily reacts with water generating flammable and/or explosive hydrogen gas and Sodium hydroxide solution

5.3 Advice for firefighters

Special protective Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

Supersedes edition of: 15.01.2009

version: 1.0 /ENG

6. Accidental Release Measures

- 6.1 **Personal** Use personal protective equipment. Avoid dust formation. **precautions:** Avoid breathing dust. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.
- **6.2 Environmental** Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Risk of explosions

6.3 Methods and material for containment and clean-up

Cover drains Pick up mechanically and arrange disposal without creating dust. Do not flush with water. Keep in suitable, closed containers for disposal. Dispose of in suitable containers

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. incompatible materials: see section 10. disposal information: see section 13.

7. Handling and Storage

7.1 Handling Keep workplace dry. Keep substance away from any moisture

Advice on safe handling

Observe label precautions. Keep workplace dry. Keep away from any moisture because substance reacts violently with water to give hydrogen gas and caustic solution of sodium hydroxide. Mixture of air and hydrogen may explode.

7.2 Storage

Storagedry, NO Sprinkler System,Requirement:Do not store together with incompatibles such as oxidizing agents, acids,
moisture. Tightly closed.
Recommended storage temperature: Room temperature

8. Exposure Controls / Personal Protection

8.1 Additional advices for design of technical equipment: provide fire extinguisher metal class D Risk of corrosion

Exposure limit values: Not applicable

8.2 Exposure controls

Engineering measures

Best available technical measures and appropriate working operations should be realized.

Dr. Bilger Umweltconsulting GmbH Gewerbepark Birkenhain 7a, 63579 Freigericht MSDS according (EG) 1907/2006 (Reach) date of issue: 21.11.2023

product: SOLVONA®

Dr. Bilger Umweltconsulting GmbH

Supersedes edition of: 15.01.2009

version: 1.0 /ENG

Personal Protection

General protection	avoid any contact with eyes and skin. No eating, drinking or smoking allowed Keep workplace dry
Respiratory Protection:	Normally there is no respiration protection necessary. In exceptional case (at example: accidental release) it is necessary to wear respiration protection.
Hand Protection:	nitrile covered cloves
	 Protective gloves must comply with the EC Directive 89/686/EEC and the related standards EN 374. Check density before use. Recommended for example:. Material: NBR (Nitril rubber) Thickness: > 0.11 mm. break through time: > 480 Minutes (Permeation level 6)
	Take rest periods to regenerate the skin. Preventive skin protection (protective creams/ointments) is recommended.
Eye Protection:	splash goggles, in exceptional cases it is necessary to wear a full length face shield

- 9. <u>Physical and Chemical Properties</u>
- 9.1 General Information
- 9.1.1 Physical state: solid
- 9.1.2 Colour: black
- 9.1.3 Odour: odourless

9.2 Important health, safety and environmental information:

- **9.2.1 Melting point (Na)** 97.85 °C
- **9.2.2 Boiling point (Na)** 892 °C
- 9.2.3 Ignition temperature (Na) 115°C
- 9.2.4 Bulk Density 0.7 kg/l
- 9.2.5 Solubility in water: violent reaction

Supersedes edition of: 15.01.2009

version: 1.0 /ENG

10. Stability and Reactivity

10.1	Reactivity	see section 10.3
10.2	Chemical stability	sensitive to moisture
	Conditions to be avoided:	High humidity, high temperature
	Compounds to be avoided:	water, oxidising agent, air, alcohol, acids
10.3	Hazardous decomposition products:	reacts violently with water to emit flammable gases and caustic solution of sodium hydroxide. Mixture of air and hydrogen may explode.
10.4 11.	Additional information Toxicological Information	in closed and undamaged packaging the BINAL is stable for several years
11.1	Acute oral toxicity	Symptoms: If ingested, severe burns of the mouth and throat, as well as a danger of perforation
	Acute inhalation toxicity	Symptoms: mucosal irritations, cough, shortness of breath, damage of respiratory tract
	Acute dermal toxicity	Causes burns
	Eye irritation	Causes serious eye damage
11.2	Additional advice:	Overexposure by skin or eye contact include skin burns or ulceration; eye corrosion with corneal or conjunctive ulceration. By inhalation of fumes the effects include irritation of the upper respiratory passages with coughing and discomfort. By ingestion, the effects include abdominal discomfort characterised by nausea, severe pain, diarrhoea and collapse.
12.	Ecological Information	
	General Information:	Sodium reacts with humidity to form sodium hydroxide in aqueous solution. The alkaline characteristics of this solution has to be regarded.
12.1 12.2 12.3 12.4 12.5 12.6	Toxicity: Persistence and degradability Bioaccumulative potential: Mobility in soil: Results of PBT and PBT/vPvB: Other adverse effects:	No information available. y: No information available. No information available. No information available. Not applicable for inorganic substances. Other ecological information Biological effects: Harmful effect due to pH shift. Possible decomposition products of possible hydrolysis are: Sodium hydroxide Entry into the environment must be avoided.

version: 1.0 /ENG

e b Dr. Bilger Umweltconsulting GmbH

> date of print: 22.11.2023 page 7 of 9

13. **Disposal Considerations**

Supersedes edition of: 15.01.2009

13.1	Product	Call the supplier for technical advice in the individual case. Pick up the material and transfer in dry drum, close tightly and store in UN-x-coded transport drum. Sodium disposal must not be attempted by inexperienced people. Transport to incineration plant according to ADR-regulation No. 4.3; I
	Large quantities Small quantities	collect in steel drum and cover with dry oil. pick up in a small steel bin, let react with Isopropanol, then add water in small quantities
13.2	Packaging	
	Steel Packaging	clean with isopropanol carefully if necessary and rinse with water before disposal. Do not drain into municipal water system.
	Emptied packaging:	Household waste or to recycling companies
13.3	Other information	The six-digit waste code is used in accordance with AVV industry-, process-type-, origin- and material-specific, Dispose of in accordance with federal, state and local regulations.
		Observe Waste Directive 2008/98/EC.

14. **Transport Information**

14.2

14.1 Rail and Road ADR/RID/GGVSE:



ADR/RID-GGVS/E class:	4.3 (W2) Material that emits flammable gases on contact with water.
Kemler-Zahl:	X423
UN-NO:	1428
Packaging Group:	
Lable	4.3
Identification:	1428 Sodium
Transport category:	1
Tunnel restriction code:	B/E
Sea IMDG/GGVSea:	
IMDG/GGVSea-class:	4.3
UN-NO:	1428
Lable	4.3
Packaging Group:	
Identification:	1428 SODIUM
EMS:	F-G S-N
Air ICAO-TI und IATA-DGR	:

14.3

ICAO/IATA-class: UN/ID-NO: Packaging Group: Identification: IATA (Passenger): IATA (cargo plane): **UN "Model Regulation ":**



UN1428, Sodium, 4.3, I

Supersedes edition of: 15.01.2009

version: 1.0 /ENG

15. <u>Regulatory Information</u>

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Major Accident Hazard Legislation	SEVESO III OTHER HAZARDS O1 / O2 Quantity 1: 100 t: quantity 2: 500 t
Occupational restrictions	Take note of Dir 94/33/EC on the protection of young people at Work

Regulation (EC) No 1006/2009 on substance that deplete the ozone layer:

not regulated

Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Dir. 79/117/EEC:

not regulated

Substances of very high concern (SVHC):

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (EACH), Article 57 above respective regulatory concentration limit of >/= 0.1 % (w/w).

16. <u>Other Information</u>

Full text of H-statements referred to under sections 2 and 3.

Training advice

Provide adequate information, instruction and training operators.

Labelling

Hazard pictograms



Signal word Danger

Hazard statements

- H260 in contact with water releases flammable gases which may ignite spontaneously
- H314 Causes severe skin burns and eye damage

e b Dr. Bilger Umweltconsulting GmbH

date of print: 22.11.2023

Supersedes edition of: 15.01.2009

version: 1.0 /ENG

EUH014 Reacts violently with water

Precautionary	statements
---------------	------------

Prevention			
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.		
Response			
P301+P330+P331	IF SWALLOWED: Rinse mouth. DO NOT induce vomiting		

I SWALLOWED. RINSE MOUTH. DO NOT INduce volniting
IF IN EYES: Rinse cautiously with water for several minutes. Remove
contact lenses, if present and easy to do. Continuous rinsing.
In case of fire: Use metal fire powder for extinction. NO WATER.
IF exposed or concerned: immediately call a POISON CENTER or
doctor/physician.

Storage

P402+P404	Store in a dry	vinlace Store	in a	closed	container
F402+F404	Slore in a ury	place. Slute	III a	CIOSEU	Container

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations. The product must not be used for any purposes other than those specified under heading 1 without first obtaining written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information given on this safety data sheet must be regarded as a description of the safety requirements relating to our product and not a guarantee of its properties

This information is taken from sources based upon data believed to be reliable. However Dr. Bilger Umweltconsulting GmbH makes no warranty as to the absolute correctness or sufficiency of any of the foregoing or that additional or other measures may not be required under particular conditions.

Local laws and regulations have to be considered by the customer upon own responsibility.